

# PEOPLE

## Smart Device DoubleL+

Real Time Monitoring Device



### Portable, Multi-use device

- Global coverage
- Self powered
- Recording 24/7
- Easily mounted
- Long battery Life
- Zero initial investment

### Application



### Certifications

- RED 2014/53/EU (incl. LVD 2014/35/EU & EMC 2014/30/EU)
- RoHS compliant
- EN 12830 (incl. ISO 27001)
- EN 60529



### Wireless connectivity

- 4G LTE Cat M1
- GPRS (2G)

### Connectivity w/ ext. sensors via Bluetooth

### Localization method

- Assisted GNSS (GPS, Glonass, Galileo, Beidou)
- Cell-locate

### Sound alarm

105 dBA@1m, 85dBA@10m

### Temp. meas. range

-30°C to 60°C (±0.2°C)

### Hum. meas. range

0 to 100% RH (±1.5%)

### Barometric meas. range

300 to 1200 mbar

### Camera characteristics

- CMOS VGA color sensor
- Images: 160×128 ~ 640×480
- Lens: 56°

### Battery

- Rechargeable LiFePO4
- Lifetime up to 18 months

### Charging

USB-C Fast Charge 3A/5V

### Data Security

- HTTPS TLS 1.3
- Blockchain method

### Data & Alarms

- Door Status
- Position/Location/Route
- Temperature
- Humidity
- Shock
- Device motion
- External motion
- Atmospheric pressure
- Tilt
- Light
- Batteries SoC
- Charging status
- Image (camera snapshot)

### On – board sensors

- Location
- Temperature
- Humidity
- Shock
- Platform motion detection
- Ext. motion detection
- Atmospheric pressure
- Tilt
- Hall effect
- Light
- Camera

### Light meas. range

0.008 to 70,000 lux (0.2%)

### PIR sensor range

12m, FOV: 69° x 69°

### Performance

- Water / dust proof IP67
- Impact resistant IK08
- UV resistant
- Chemicals resistant
- Flame-proof

### Other Features

- Recording
- Real-time alarms
- OTA FW update
- OTA configuration
- Inter-devices communication
- Global coverage
- Communication with backend system & mobile app

### Services

- 24/7 Recording
- Alarms
- Notifications
- Auto-reporting
- Analytics
- Tracing
- Insights

Designed and developed  
by PEOPLE  
www.people-t.com